




新品



技术特点：

圆锥形喷嘴头特别适合常规清洗作业以及住宅排污管道的疏通清洗。可根据使用环境的不同，例如污水或水循环系统来选择不锈钢喷嘴或陶瓷喷嘴。陶瓷喷嘴的使用寿命比不锈钢喷嘴长。

应用范围：

- 住宅排污管道疏通
- 垂直管道清洗
- 碎屑、碎石、皂液和油污清洗
- 公共卫生间清洗

型号	编号	 流量	 最大压力	额定温度	接口规格	侧喷嘴数量	前喷嘴数量	喷嘴尺寸	孔径	清洗管道内壁直径	 重量	 件/箱	维修包编号	 件/箱	
		bar	psi						Ø mm	mm	g	件/箱		件/箱	
SN管道疏通喷嘴	4052600003	见图表 	300	4350	160℃	1/2" GF	6-M 6x8	1-M 6x8	20	28 x 42	50÷100	80	1	4059900032	1
	4052600004		300	4350	160℃	1/2" GF	6-M 6x8	1-M 6x8	30	28 x 42	50÷100	80	1	4059900033	1
	4052600005		300	4350	160℃	3/4" GF	6-M 6x8	1-M 6x8	30	35 x 62	60÷130	250	1	4059900033	1
	4052600018		300	4350	160℃	3/4" GF	6-M 6x8	1-M 6x8	40	35 x 62	60÷130	250	1	4059900034	1
	4052600019		300	4350	160℃	3/4" GF	6-M 6x8	1-M 6x8	50	35 x 62	60÷130	250	1	4059900035	1
	4052600020		300	4350	160℃	3/4" GF	6-M 6x8	1-M 6x8	60	35 x 62	60÷130	250	1	4059900036	1
	4052600021		300	4350	160℃	1" GF	6-M 6x8	1-M 6x8	50	45 x 66	80÷150	380	1	4059900035	1
	4052600022		300	4350	160℃	1" GF	6-M 6x8	1-M 6x8	60	45 x 66	80÷150	380	1	4059900036	1
	4052600023		300	4350	160℃	1" GF	6-M 6x8	1-M 6x8	80	45 x 66	80÷150	380	1	4059900037	1
	喷嘴罩维修包编号													U00001030	1

材质：镀镍钢